



**152-[\*]-[\*\*]-[\*\*\*]-[F]**      Category-3

\*Type of shield; Options are:

- S** = Shielded without tabs
  - ST** = Shielded with tabs
  - P3** = Shielded with conductive gasket
  - Blank** = Unshielded
- A** = Alternate ground tab option available only for single port connectors (Add A after type of shield e.g. 155-STA-8-8)

\*\*Number of contacts; Options are:

- 8** = 8 positions, 8 contacts

\*\*\*Number of ports; Options are:

- 1** = 1 Port      **6** = 6 Port
- 2** = 2 Port      **8** = 8 Port
- 4** = 4 Port      **12** = 12 Port

**F** = Ferrite filter option; Available only for CAT-3

**FEATURES:**

- Up to 10dB EMC improvement over competition
- More efficient with conductive gasket
- Fits existing designs and port openings
- Easier to mount
- No bent or broken tabs
- No masking or precise cutouts required
- Better seal keeps dust, and moisture out
- Offers an edge in world markets on compliance issues
- Available with optional ferrite filters for frequency Applications such as modems
- FCC 68 sub part F compliant
- 50µ" Gold on contacts standard

**MATERIAL:**

- Housing: UL94V-0 / PBT glass filled
- Shield: Tin plated copper alloy
- Contacts: Phosphor bronze 50µ" gold over nickel

**Attenuation of interfering signal reference to chassis using the P3 EIGHT port connector**

