

Modular Jack Selector



High Performance RJ 45 - Category 5 Series

Right Angle	Part Series	EMI Gasket	Shielded	Shielded / Enhanced Tabs	Unshielded	Ferrite Filter Option	Hi Temp Option on Single Ports	Features
<p>Hi Speed EMI Performance</p>	155P3	X	X			X	X	<ul style="list-style-type: none"> Patented Hi Speed Microwave contact design. Exceeds TIA / EIA 568A Crosstalk Standards.
	155S		X			X	X	<ul style="list-style-type: none"> Category 5, 5E & Gigabit ready. Configurations: 1, 2, 4, 6, 8 Ports.
	155ST			X		X	X	<ul style="list-style-type: none"> P3 Gasket improves EMI Performance up to 10db. Tested to 1,000 insertions.
	155				X	X	X	<ul style="list-style-type: none"> Alternate Ground Tabs available on 1-Port version. Single port available on Tape and Reel.

Stacked	Part Series	EMI Gasket	Shielded	Shielded / Enhanced Tabs	Unshielded	Ferrite Filter Option	Features
<p>EMI Master</p>	255P3	X	X			X	<ul style="list-style-type: none"> Patented Hi Speed Microwave Contacts design. Category 5, 5E & Gigabit ready. Exceeds TIA/EIA 568A Crosstalk Standards.
	255ST			X		X	<ul style="list-style-type: none"> P3 Gasket improves EMI Performance up to 10db. Configurations: 2X4, 2X6, 2X8.

Vertical	Part Series	EMI Gasket	Shielded	Panel Stop Option	Unshielded	Ferrite Filter Option	Features
	258 - C5		X	X	X		<ul style="list-style-type: none"> Exceeds Category 5 Performance 50µ " gold FCC Part 68 sub part F compliant.

In-Line Coupler	Part Series	EMI Gasket	Shielded	Snap-In Design	Unshielded	UL/CSA Approved	Features
	M1026KS-C5		X	X		X	<ul style="list-style-type: none"> Exceeds Category 5 performance. Ideals for feedthru / panel applications. Mates with Regal 1003B plugs. Metal shield for EMI protection.

High Performance RJ 45 - Category 3 Series

Right Angle	Part Series	EMI Gasket	Shielded	Shielded / Enhanced Tabs	Unshielded	Ferrite Filter Option	Features
	152P3	X	X			X	<ul style="list-style-type: none"> FCC Part 68 sub part F compliant.
	152S		X			X	<ul style="list-style-type: none"> 50µ " gold standard on contacts.
	152ST			X		X	<ul style="list-style-type: none"> Configurations: 1, 2, 4, 6, 8 ports.
	152				X	X	<ul style="list-style-type: none"> P3 Gasket improves EMI Performance up to 10db.

Standard RJ 45 - Category 3 Series

Commercial Series Right Angle	Part Series	Hi Temp Option	Shielded	Shielded / Enhanced Tabs	Unshielded	Ferrite Filter Option	Features
<p>New</p> <p>Economical</p>	152CST		X		X		▼ Available in 15, 30 & 50µ " of gold plating.
	152CS	X			X		▼ Configurations: 1, 2, 4, 6, 8 Ports.
	152C			X	X		▼ Filter option designed for Telco applications.

Low Profile	Part Series	Front Shielded	Shielded / Enhance Tabs	Unshielded	11.5 mm Height	12.4 mm Height	Panel Stop Option	Features
	153	X		X		X		▼ As low as 8.65 mm high.
	951		X	X	X			▼ Available in 15, 30 & 50µ " of gold plating.
	453	X		X		X	X	▼ 6, 8 or 10 contacts available.

Vertical	Part Series	Surface Mount	Shielded	Panel Stop	Unshielded	Multiport Availability	Features
	258		X	X	X		▼ Standard 6µ " of gold plating; 50µ " option available.
	258S		X		X		▼ Low .650 profile
	258 SMT	X	X		X		▼ Configurations: 1, 2, 4, 6 Ports. Available in 6 or 8 Contact.

45° Entry	Part Series	Shielded	Unshielded	Gold Plating Options	Features
	WV45	X	X		▼ Available in 15, 30 & 50µ " of gold plating.
	UV45		X	X	▼ Standard color: White.

In-Line Coupler	Part Series	Full Shield	Unshielded	Panel Stops	Metal Tabs	Plastic Tabs	Crosswire Telco Option	Features
	M1026KS-MM	X	X	X				▼ 50µ " gold on contacts. Available in 6 or 8 contact.
	M1026K		X	X		X		▼ Meets FCC Part 68.
	M1026KS	X		X		X	X	▼ Mates with Regal 1001 Series plug.

Low Profile Surface Mount	Part Series	Shielded	Shielded / Enhanced Tabs	Unshielded	Ultra Low Profile	8.65 mm Height	11.5 mm Height	Features
	951 - SMT	X	X				X	▼ Temperature rating: 55° C to 125° C.
	453-SMT	X			X	X		▼ Standard 6µ " of gold plating; 15, 30 & 50µ " available.



RJ 11 Series Modular Jacks

Right Angle	Part Series	Shielded	Unshielded	Multiport Availability	Low Profile	Features
	249		X			▼ Contact options: 6P2C, 6P4C & 6P6C.
	353	X			X	▼ Standard 6μ " of gold plating.
	544		X	X		▼ Low cost design.
	950		X		X	▼ Configurations: 1, 2, 4, 6, 8 Ports.
						▼ UL94V-O / PBT glass filled housing.


Vertical	Part Series	Shielded	Unshielded	Multiport Availability	Panel Stops	Features
	258		X	X	X	▼ 6P4C and 6P6C Contact options.
	547		X	X		▼ Configurations: 1; 4 Ports.
	258S	X		X		▼ Standard 6μ " of gold plating; 15, 30 & 50μ " available.


Surface Mount	Part Series	Shielded	Unshielded	Tape & Reel	11.5 mm Height	Features
	951-SMT	X	X		X	▼ Temperature rating: 55° C to 125° C.
	954-SMT	X	X	X	X	▼ Contact options: 6P2C, 6P4C & 6P6C.
						▼ Standard 6μ " of gold plating; 15, 30 & 50μ " available.

Surface Mount Ultra-Low Profile	Part Series	Shielded	Unshielded	Ultra Low Profile	Features
<p>New</p> <p>Thru-board design</p>	353-SMT	X	X	X	▼ Only 8.65 mm high. ▼ Contact options: 6P6C, 6P4C, 6P2C. ▼ Standard 6μ " of gold plating; 15, 30 & 50μ " available.


Prewired Jacks	Part Series	Shielded	Unshielded	Panel Mount	Features
	623P	X	X		▼ Contact configurations: 6P6C, 6P4C, 8P8C.
	641D	X	X		▼ Prewired with 7" 26 AWG and spade lugs.
					▼ Colors: Gray or black.


Modular Plugs


RJ45	Part Series	Shielded	Category 3	Category 5	24 & 26 AWG	28 AWG	Features
		1001-8	X		X		
1003B	X	X					
1003B-C5	X		X	X			
1004B	X	X				X	


RJ 11	Part Series	4 Position	6 Position	Features
		1001-4	X	
1001-6		X		

USB Sockets

Right Angle	Part Series	Single Port	Stacked	Side Mount	SMT Option	Features
		90A (A Type)	X		X	
90B (B Type)	X					
90D (A Type)		X				

Vertical	Part Series	Single Port	Stacked	Top Entry	SMT Option	Features
		90S-A-S	X		X	
90S-B-S	X		X			

Mini SMT Right Angle	Part Series	Single Port	Side Mount	SMT Option	Features
		91-A (A Type)	X		
91-B (B Type)	X			X	

IEEE 1394	Part Series	Single Port	Stacked	Side Mount	SMT Option	Features
		901-1394	X		X	
Firewire						